

# QUICKSTYLE

Floors That Set Us Apart



**Athens**  
2084-WYS-K14130-F

# APOLLO

ENGINEERED WOOD COLLECTION



**Tripoli**  
2084-BLR-K14130-F



**Delphi**  
2084-CBR-K14130-F



**Argos**  
2084-P9R-K14130-F



**Athens**  
2084-WYS-K14130-F



**Anatolia**  
2084-WAH-K14130-F

# ENGINEERED WOOD COLLECTION

Dimension	5 1/8" x 43" (130.18 mm x 1092.2 mm)
Packaging	7
Weight/Box	8.165 (18.79 lbs.)
Installation	Click installation, Glue down, Nail down
Construction	2.5mm Select European White Oak
Core	Core Coniferous layers
Thickness	14.0 mil

Classification of the surface layer according EN 13489	Free class
Classification of the surface layer	Family class
Healthy knots	Acceptable up to 1 - 3/8" (35 mm) in diameter
Unhealthy knots with fillin, scattered	Acceptable up to 1" (25 mm) in diameter
Unhealthy holes from knots	Acceptable up to 13/16"(20 mm) in diameter
Bark pockets	Acceptable
Colour scheme of surface layer	Varied, depending on wood type
Arrangement of fibres	Varied
Flecking	Acceptable , without limit
Mineral grains	Acceptable , without limit
Sapwood	Acceptable, on the edge up to max 10% wide
Filling cracks in filled	Acceptable up to 3/16"(5 mm) wide, up to 7-7/8" (200 mm) length
Biodegradation of surface layer	Unacceptable

\* According to the EN 13489 standard, 3% of different grade than indicated is acceptable. The limits of characteristic features of the product concern the upper layer of the element. The knots' fillings, especially in case of brushed surfaces, can be characterized by gaps which a deliberate effect of this kind of decorative surface. Measurement of wood characteristics according to EN 1310 standard. Dimensional characteristics and acceptable deviations (consistent with standard PN-EN 13489). Dimensional characteristics and dimensional tolerances, marked at the time of leaving the manufacturer's facility, given in accordance with the type of multi-layer flooring elements.

Thicknesses boards measured in according with EN 13647

Actual dimensions(mm)	Actual tolerances	Nominal dimensions (inch)	Nominal tolerances
Thickness: 14	Gap (between elements) ≤ 0,2 mm	Thickness: 9/16	Gap (between elements) ≤ 0,008"
Length: 1092	+/-0,1%	Length: 43	+/-0,1%
Width: 130	+/- 0,2mm	Width: 5-1/8	+/- 0,008"
	Actual dimensions (mm)	Nominal dimensions (inch)	
Number of boardson a pack:	7 pcs. x 1092 v 6 pcs. x 1092+ 1 pcs. x 1064	7 pcs. x 43 v 6 pcs. x 43 + 1 pcs. x 41,89	
Surface layer:	Actual 2,5mm (Nominal 0,098")		
Core (middle and bottom layer):	Actual 11,5mm (Nominal 0,453")		
Pack:	0,99m2/pack, 49 pack/pallet = 48,51m2	10,65ft2/pack, 49 pack/pallet = 522,157ft2	

Product description:	Product consists of three layers: surface layer – oak, middle and bottom layer - pine
Top layer:	One row of strips, Family grade
Finish surface Layer:	Acrylic matte lacquer, UV hardened. Gloss level (Gardner scale) 7°-11°
The connection system boards: (for each package includes instructions assembly)	Cross edge - Barlock 5Gc system, transverse lock insert – HDF Contains hardwood plywood US EPA TSCA Title VI and CARB 2 compliant.
Surface appearance	Yellow-brown oak wood with natural features characteristic for this kind. The floor is characterized by grain variability and varied colours. It darkens under the influence of UV rays, four-sided microbevelled top layer, structured by brushing. Coloured product, colour: white.
Hardness oak applied to the top layer of the board. The method according testing Janka	650-1000 kG/cm <sup>2</sup> (rating IV, hardwood)
Humidity board:	7% +/- 2%
Installation on underfloor heating system:	Product designed in the system of electric and water floor heating solution. For each package includes instructions assembly.
Limited warranty:	30 years residential, 5 years commercial

**ATTENTION:** The natural features of the wood make every product a unique and unrepeatable item. Individual photographs in the sample books do not fully reflect the appearance of the product.

The engineered wood flooring should be cared for using only agents intended for this purpose. The manufacturer and Quickstyle bears no responsibility for the effects of using agents made by other manufacturers.

**ATTENTION:** Before applying any third party care product be sure to test it on a concealed area of the floor to assess whether or not there is a negative reaction of lacquer on the floorboard (for example, discoloration or peeling). Regular care of lacquer floors conceals minor wear and tear of everyday use. The greatest enemies of wooden floors are water and sand. In case of soiling of the floor, these should be carefully and gently remove



### Pet Friendly

Easy to maintain flooring for messy pets



### 100% Waterproof

Made of fully waterproof material



### Canadian Innovation

Designed by a Canadian based company



### Non-Toxic

Created with non-toxic materials with the environment in mind



### FloorScore Certified

Indoor air quality certification standard for hard surface flooring materials



### 30 Residential Structural Warranty

Cover the repair or replacement of a product within a residential setting for life in accordance with the Quickstyle's warranty terms