QUICKSTYLE

Floors That Set Us Apart



METROPOLIS

VINYL GLUE DOWN



Victoria 300-VL88174L-001



Savile 300-VL88206L-004



Abbey 300-VL88218L-004



Jasper 300-VL88231L-004



Saint Laurent 300-VL88292L-005

Dimension	7.25" X 48" (184 mm X 1219 mm)	
Packaging	16	
Weight/Box	19.73 kg (43.48 lbs.)	
Square Feet/ Box	38.670 ft ² (3.592 m ²)	
Installation	Glue	
Construction	Vinyl	
Total Thickness	3.0 mm	
Wear Layer	20MIL	

Construction:	Standard	Performance - results
Classification:	ASTM F1700	Class III, Type A - Smooth, Type B Embossed
Squareness:	ASTM F2421	Passes - ±0.10" max
Size and tolerance:	ASTM F2055	Passes - ±0.016 in. per linear foot
Thickness:	ASTM F386	Passes - as specified ±0.005"
Flexibility:	AASTM F137	Passes - 1" mandrel
Dimensional stability:	ASTM F2199	Passes - 0.020"/linear foot max
Static load:	ASTM F970	Passes, modified at 1000 psi
Residual indentation:	ASTM F1914	Passes - Average less than 8%, maximum single reading 10%
Resistance to chemical	ASTM F925	Passes - No more than a slight
change		
Resistance to light:	ASTM F1515	Passes - ΔE < 8
Resistance to heat:	ASTM F1514	Passes - ΔE < 8
Critical radiant flux:	ASTM E648	Passes - ≥ 0.45 watts/cm², Class 1
Smoke density:	ASTM E662	Part A - Less than 450

Warranties

Limited Lifetime Residential Warranty 15 Years Light Commercial Warranty