



L-723-FC062-12 - Monviso



L-723-FSX06-12 - Denali



L-723-FSX07-12 - Santis



L-723-FW004-12 - Ventoux



L-723-FXL038-12 - Mousa

ALPINE LAMINATE 12 MM TECHNICAL SPECIFICATIONS

Dimensions	7 5/8" x 47 5/16" (195 mm x 1202 mm)
Packaging	8
Coverage/Box	20.184 ft² (1.875 m²)
Installation	DropLock
Thickness	12 mm – Water Resistant
Surface	Oxyde d'Aluminium Grade AC5 – Carb 2

TECHNICAL DATA SHEET		12 MM - CLASS 33 - AC5	
THICKNESS	mm	12	EN 13329+A1
WIDTH	mm	195	EN 13329+A1
LENGHT	mm	1202	EN 13329+A1
SURFACE		Country - Vintage	
EUROPEAN STANDARD	-	 AC5 12 HOUR COMPROMISE FREE WARRANTY	EN 13329
PACKAGE DETAILS			
PIECE		8 piece / 1 package	
M2		1,87 m²	
KG		20,5 kg	
PALLET DETAILS			
PIECE		50 package / 1 pallet	
M2		93,5 m²	
KG		1030 kg	
CLASS ABRASION RESISTANCE	-	33	EN 13329+A1
	-	AC5	EN 13329+A1
THICKNESS SWELLING	%	≤15	ISO 24336
RESISTANCE TO IMPACT	SMALL BALL	N	≥15
	LARGE BALL	mm	≥1000
WARRANTY DOMESTIC / COMMERCIAL	Years	25/15	-
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438-2_5
SURFACE SOUNDNESS	N/mm²	≥1.25	EN 13329+A1
LOCK STRENGTH	LENGHT WIDTH		ISO 24334
EFFECT OF A CASTOR CHAIR	25.000cycles		EN 425:2002
EFFECT OF A FURNITURE LEG	-	kN/m	f10,2 ≥ 1
OPENING BETWEEN ELEMENTS		kN/m	fs0,2 ≥ 2
HEIGHT DIFFERENCE BETWEEN ELEMENTS			No Damage
MOISTURE CONTENT			No Damage
FIRE RESISTANCE		mm	≤0,20
		mm	≤0,15
		%	4-10
	Class	C _n S1	EN 9239-1
FORMALDEHYDE RELEASE	mg/m²h	≤3,5 (E1)	EN 12460-3
SLIP RESISTANCE	Class	DS	EN 13893:2003
IMPACT SOUND REDUCTION	dB	15	EN ISO 10140-3
THERMAL RESISTANCE	(m2K)/W	0,08	EN 12667:2001