



Victoria
300-VL88174L-001



Savile
300-VL88206L-004



Abbey
300-VL88218L-004



Jasper
300-VL88231L-004



Saint Laurent
300-VL88292L-005

VINYL GLUE DOWN METROPOLIS - TECHNICAL SPECIFICATIONS

Dimension	7.25" X 48" (184 mm X 1220 mm)
Packaging	16
Weight/Box	19.72 kg (43.48 lbs.)
Coverage/ Box	38.67 ft ² (3.592 m ²)
Installation	Glue Down
Construction	Vinyl
Thickness	3.0 mm
Wear Layer	0.5 / 20 MIL

Construction	Standard	Performance - results
Classification	ASTM F1700	Class III, Type A - Smooth, Type B Embossed
Squareness	ASTM F2421	Passes - $\pm 0.10"$ max
Size and tolerance	ASTM F2055	Passes - ± 0.016 in. per linear foot
Thickness	ASTM F386	Passes - as specified $\pm 0.005"$
Flexibility	A ASTM F137	Passes - 1" mandrel
Dimensional stability	ASTM F2199	Passes - 0.020"/linear foot max
Static load	ASTM F970	Passes, modified at 1000 psi
Residual indentation	ASTM F1914	Passes - Average less than 8%, maximum single reading 10%
Resistance to chemical change	ASTM F925	Passes - No more than a slight
Resistance to light	ASTM F1515	Passes - $\Delta E < 8$
Resistance to heat	ASTM F1514	Passes - $\Delta E < 8$
Critical radiant flux	ASTM E648	Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke density	ASTM E662	Part A - Less than 450