

UNDERLAYMENTS

Cross-linked EPE Foam with PE Film

8161-DB-10



Product Details:

43.3" X 27.72' - 2mm

100 ft² / roll

1.10 m x 8.45m

9.29 m²

Density: 25 KG/m³

- Cost effective
- Minimal Sound insulation
- Lip and Tape ensure quick installation
- IIC: up to 45 dB
- STC : up to 45 dB

*IIC and STC may vary depending on the building materials and structure

Cross-linked EPE Foam with Aluminum Heat Reflector Vapor Barrier

8161-DB-20



Product Details:

43.3" X 27.72' - 2mm

100 ft² / roll

1.10 m x 8.45m

9.29 m²

Density: 25 KG/m³

- Cost effective
- Aluminium Heat Reflector vapor Barrier
- Moisture proof
- Minimal Sound insulation
- Lip and Tape ensure quick installation
- IIC: up to 45 dB
- STC : up to 45 dB

*IIC and STC may vary depending on the building materials and structure

EVA Foam with Aluminum Heat Reflector Vapor Barrier

8161-DB-30



Product Details:

48" X 25.4' - 2mm

100 ft² / roll

1.20 m x 7.75 m

9.29 m²

Density: 110 KG/m³

- Better Sound insulation
- Moisture proof
- Heat preservation
- Excellent physical performance
- Lip and Tape ensure quick installation
- IIC: Up to 69 dB
- STC: Up to 67 dB

*IIC and STC may vary depending on the building materials and structure

QUICKSTYLE

Des Planchers Qui Nous Distinguent • Floors That Set Us Apart
www.quickstyle.com • 1-800-387-8953 • info@quickstyle.com